



## H&B Copper-Tuff™

### Copper Thru-Wall Flashing

A patented super-strong polymer coating is bonded to a copper sheet for maximum performance. A fiberglass scrim is embedded between this coating and copper for excellent puncture and tear resistance.

#### U.S. Pat. No. 6,928,780 Patents Pending

- Available with 3, 5, or 7 oz. copper sheet.
- UV-resistant for up to 180 days.
- Compatible with ACQ and all other treatments for pressure-treated lumber.
- Asphalt-free composition compatible with a wide variety of sealants.
- Available in widths from 12"-36", other widths available upon request.
- 25' long roll.

#### Technical Data

- Copper sheet used in the fabrication of H&B copper laminates conforms to - **ASTM B370-03 (110 Alloy)**

#### Sizes (Rolls are 25 ft. long)

- Widths:  12"  16"  18"  20"  24"  
 32"  36"  Other \_\_\_\_\_

#### St/Steel Drip Plate

- 1-1/2"  3"  Other \_\_\_\_\_

#### Flex-Flash® Drip Edge

- 1-1/2"  3"  Other \_\_\_\_\_

#### Termination Bar

- Stainless Steel (*Type 304*)  
 Aluminum  
 Plastic

#### H&B 1-Quart Mastic Tube

H&B Primer 36 (5 gal. pail)

H&B Mastic (5 gal. pail)