



HOHMANN & BARNARD, INC.
A MiTek - BERKSHIRE HATHAWAY COMPANY

Flashing and Reglets

SANDELL'S TROWEL MASTIC



DESCRIPTION

A cut-back asphalt, containing long-fibered material, manufactured in proper consistency for easy application. It is manufactured to a trowel grade consistency which will provide durable, elastic coating highly resistant to weathering while providing excellent adhesion properties. Sandell Trowel Mastic performs well over a wide range of temperature and weather conditions. It complies with all requirements of Federal Specifications SS-C—153, Type 1 and ASTM 4586-88, Type 1 and SSPC No. 12.

USES

Copper Laminated Flashings

Splicing:

Sandell Asphalt Trowel Mastic is the preferred mastic to be used while splicing copper flashings. Material should be overlapped a minimum of 4" and coating of Sandell Asphalt Trowel Mastic applied to a yield of 25 sq. ft. per gallon coverage.

Vertical Masonry Surfaces:

Sandell Asphalt Trowel Mastic should be spotted to vertical surfaces to receive flashing. Sandell Asphalt Trowel Mastic will hold the flashing in place while masonry is set. Flashing should be secured in a reglet or masonry joint or mechanical fastener.

General Purpose:

Sandell Asphalt Trowel Mastic can also be used as a general purpose cement for repairing leaks in asphalt roofs, metal roofs, chimneys, flues, down spouts and concrete.

CONSISTENCY

Sandell Asphalt Trowel Mastic is a heavy, trowel grade which spreads easily and adheres to most surfaces. Coverage should yield approximately 25 sq. ft. per gallon. Sandell Asphalt Trowel Mastic retains its elasticity coating will resist extreme and ductility, thus variations in temperature.

SURFACE PREPARATION

All surfaces should be clean, dry, and free from grease, oil, or other loose foreign matter.

PACKAGE SIZE

Available in:

5-gallon pails 30 oz. tubes

PHYSICAL PROPERTIES

Boiling Point:	650°F (343°C)
Flash Point and Method:	110°F (43°C)
Solubility in Water:	None
Appearance:	Black Paste



HOHMANN & BARNARD, Inc.
30 Rasons Court | Hauppauge, NY 11788
CORPORATE HEADQUARTERS
T: 800.645.0616 F: 631.234.0683
www.h-b.com

Branch/Subsidiary Locations:
ALABAMA - ILLINOIS - MARYLAND
NEW YORK - PENNSYLVANIA - TEXAS
CANADA

© HOHMANN & BARNARD, INC. - 2013